



RDS-30

Radiation Survey Meter

- gamma ambient equivalent dose rate measurement $H^*(10)$
- measurement range from 0.01 $\mu\text{Sv/h}$ to 100 mSv/h or from 1 $\mu\text{rem/h}$ to 10 rem/h

- small size and large display
- measurement in $\mu\text{Sv/h}$ or mrem/h
- gamma dose indication
- visual and audible signalling
- high battery life time (> 1 year)
- compliant to IEC 60846

The RDS-30 Radiation Survey Meter is a versatile gamma radiation detector which has been designed for a wide range of applications involving a possibility for abnormal radiation levels.

Compact, lightweight, waterproof, its performance and its user friendly interface make the RDS-30 perfectly suited to radiation survey in field conditions as in nuclear industry or for protection against radiological hazards.

Physical characteristics

- **radiation detected:**
 - gamma and X-ray from 48 keV to 1.3 MeV
- **detector:**
 - energy compensated GM tube compliant to H*(10)
- **dose rate measurement range:**
 - from 0.01 µSv/h to 100 mSv/h or from 1 µrem/h to 10 rem/h
- **dose rate linearity:**
 - ± 10 % ±1 digit within the range of 0.1 µSv/h to 100 mSv/h or 10 µrem/h to 10 rem/h
- **calibration accuracy:**
 - ± 5 % of the reading in ¹³⁷Cs exposure, at 3 mSv/h, +20°C (68°F)
- **energy response:**
 - ± 30 % over the range of 48 keV - 1.3 MeV
- **angular response:**
 - ± 25 % within ± 45 % from the calibration direction at 48 keV
- **dose measurement range:**
 - from 0.01 µSv to 1 Sv or from 1 µrem to 100 rem

Functional characteristics

- dose rate follow-up by audible signal with frequency proportional to dose rate
- visual and audible alarm: user settable for dose and dose rate over the whole measurement range
- dose measurement
- histogram capability of up to 480 dose rate values with user settable logging interval
- backlit display with six large digits
- display in either µSv/h or in mrem/h
- built-in self diagnostics

Electrical characteristics

- power supply: 2 alkaline batteries IEC LR6/AA size (recommended)
- battery life time: at least 2000 hours at normal background with alkaline cells (more than 1 year under normal operation)
- battery alarm: two-step alarm for low battery voltage
- electromagnetic compatibility: CE compliant

Accessories

- software for parameter setting and histogram readings
- wrist strap
- neck strap

Mechanical characteristics

- **case:**
 - rugged plastic, easily decontaminable
- **dimensions:**
 - 78 x 126 x 32 mm
- **weight:**
 - 170 g without batteries
 - 220 g with batteries

Environmental characteristics

- **temperature range :**
 - -25 ... +55°C operational (-13... 131°F)
 - -40 ... +70°C storage (-40... 158°F)
- **protection level:**
 - IP67 (temporary immersion / floating device)

External interfaces

- Built-in infra-red port (IrDA)

130665C

Lamanon - France
Turku - Finland
Hamburg - Germany
Munich- Germany
Smyrna (GA) - USA
Other countries

Tel +33 (0)4 90 59 5959
Tel +358 2 4684 600
Tel +49 40 85193-0
Tel +49 (0) 89 51 51 30
Tel +001 (770) 4322744
Tel +33 (0)4 90 59 60 41

Representative address:

As standards, specifications and design change from time to time, please ask for confirmation of the information given in this publication.